



Bookeye® GS400

Overview of main functions

- Format selection up to DIN A1
- 56 mega-pixel resolution
- 1024 gray levels internal;
256 gray levels external
- Automatic exposure control
- Autofocus
- Automatic page separation
- Automatic book-fold correction
- PDF conversion
- Simple installation
- Self calibrating
- User friendly

ImageWare continues the development of its product portfolio with the Bookeye® GS400 gray-level scanner.

The Bookeye® GS400 can easily be integrated in existing company networks. With the standard TCP/IP interface the device can be connected wherever there is a free network socket.

Special video boards, drivers and effort for integration are a thing of the past. Plug it in and off you go!

Your advantage: immediate productivity plus cost and time savings.

Overview of most common originals

- Books
- Colored architectural plans
- Colored wiring diagrams
- Maps and drawings
- Colored newspapers and periodicals
- Atlases
- Ancient manuscripts
- Surveys with photos
- Quality control and documentation
- Graphical designs

Technical Data	Original Formats	Scanning	Accessories
h x w x d: 880 x 685 x 673 mm	Max. w x d: 594 x 425 mm	Resolution: 200, 300, 400 dpi	Automatic book cradle
Weight: 25 kg (38 kg incl. pack.)	DIN A4 ✓ DIN A3 ✓ DIN A2 ✓ DIN A1 ✓	Scan time: DIN A4 portrait 2 sec DIN A3 landscape 2,2 sec DIN A2 landscape 3 sec	Special keypad
Voltage: 115 V		Color depth: internal 1.024 gray levels external 256 gray levels	Paper and slide smoother
Frequency: 60 Hz		Interface/protocol: TCP/IP	Foot switch
Power: max. 250 VA		Software: BCS-2	Coin slot
Lamps: UV- and IR-free cold lamps approx. 3000 Lux			Copy card



All trademarks are registered trademarks of their owners.
Subject to change without notice. No liability is accepted for errors or misprints.
© ImageWare Components GmbH 2003